



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G9962ZX 24" 10 HP 3-PHASE WIDE-BELT SANDER

### Product Dimensions:

Weight..... 1650 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 40 x 50 x 68 in.  
Footprint (Length x Width)..... 39-3/8 x 19-5/16 in.

### Shipping Dimensions:

Type..... Wood Slat Crate  
Content..... Machine  
Weight..... 1518 lbs.  
Length x Width x Height..... 52 x 44 x 78 in.  
Must Ship Upright..... Yes

### Electrical:

Power Requirement..... 220V or 440V, 3-Phase, 60 Hz  
Prewired Voltage..... 220V  
Full-Load Current Rating..... 29.6A at 220V, 14.8A at 440V  
Minimum Circuit Size..... 40A at 220V, 20A at 440V  
Connection Type..... Permanent (Hardwire to Shutoff Switch)  
Switch Type..... Control Panel w/Magnetic Switch Protection  
Voltage Conversion Kit..... P9962ZX9139 (O/S) or P9962ZX9139A (N/S) for 440V  
Recommended Phase Converter..... H3742

### Motors:

#### Main

Horsepower..... 10 HP  
Phase..... 3-Phase  
Amps..... 25A/12.5A  
Speed..... 1750 RPM  
Type..... TEFC Induction  
Power Transfer ..... Twin V-Belt Drive  
Bearings..... Sealed & Permanently Lubricated  
Centrifugal Switch/Contacts Type..... N/A

#### Table Elevation

Horsepower..... 1/4 HP  
Phase..... 3-Phase  
Amps..... 1.2A/0.6A  
Speed..... 1650 RPM  
Type..... TEFC Induction  
Power Transfer ..... V-Belt Drive  
Bearings..... Sealed & Permanently Lubricated  
Centrifugal Switch/Contacts Type..... N/A

**Feed**

Horsepower..... 1 HP  
Phase..... 3-Phase  
Amps..... 3.4A/1.7A  
Speed..... 1700 RPM  
Type..... TEFC Induction  
Power Transfer ..... V-Belt Drive  
Bearings..... Sealed & Permanently Lubricated  
Centrifugal Switch/Contacts Type..... N/A

**Main Specifications:**

**Operation Information**

Number of Sanding Heads..... 1  
Maximum Board Width..... 24-3/8 in.  
Minimum Board Width..... 2 in.  
Maximum Board Thickness..... 6 in.  
Minimum Board Thickness..... 1/8 in.  
Minimum Board Length..... 10 in.  
Sandpaper Speed..... 3500 FPM  
Sanding Belt Oscillations per Minute..... 5/8 – 3/4 in.  
Conveyor Feed Rate..... 15 – 49 FPM  
Sandpaper Length..... 60 in.  
Sandpaper Width..... 25 in.

**Drum Information**

Infeed Sanding Drum Type..... Spiral Grooved Rubber  
Infeed Sanding Drum Size..... 8 in.  
Shore Hardness (Durometer)..... 65 Shore

**Construction**

Conveyor Belt..... Rubber  
Body..... Steel  
Paint Type/Finish..... Powder Coated

**Other Related Information**

Floor To Table Height..... 30 in.  
Belt Tracking..... Pneumatic  
Sanding Belt Tension..... Pneumatic  
Number of Pressure Rollers..... 4  
Pressure Roller Type..... Rubber  
Pressure Roller Size..... 2 in.  
Conveyor Belt Length..... 84-1/2 in.  
Conveyor Belt Width..... 24-9/16 in.  
Belt Roller Size..... 4 in.  
Number of Dust Ports..... 2  
Dust Port Size..... 5 in.  
Air Requirement..... 75 PSI

**Other Specifications:**

Country of Origin ..... Taiwan  
Warranty ..... 1 Year  
Approximate Assembly & Setup Time ..... 1 Hour  
Serial Number Location ..... ID Label Below Grizzly Nameplate  
ISO 9001 Factory ..... Yes  
Certified by a Nationally Recognized Testing Laboratory (NRTL) ..... Yes

**Features:**

- Pneumatic Belt Tensioning
- Industrial-Duty Rubber Conveyor Belt
- Two 5" Dust Ports
- Variable-Speed Feed Conveyor
- Amp/Load Meter
- Built-In Air Regulator/Water Separator
- Independent Motor Controls for Sanding Drums, Table Elevation and Conveyor
- Disc Brake
- Emergency Stop Bar
- Adjustable Sanding Belt Oscillation Speed
- Single Sanding Drum
- Dual Rubber Infeed and Outfeed Pressure Rollers
- Sturdy 4-Column Table Lifting and Lowering System
- Powered Table Elevation with Keypad for Typing/Storing Exact Measurements
- Digital Readout Displays Table Height in Increments of 0.005" for Super-Accurate Results